



ALL FOREIGN MATERIAL SHALL BE REMOVED FROM THE SAWCUT AND FROM THE SURFACE OF THE SURROUNDING AREA. THE HOLE OR SAWCUT AND ITS SURROUNDING SURFACE SHALL BE FREE OF STANDING WATER BUT IN WATER SATURATED DRY CONDITION FOR RESTORATION.

ANY EXCESS OF THIS MIXTURE THAT OVERFLOWS THE CUT IS TO BE REMOVED.

THE CUT IS BACKFILLED BY POURING 1118 FUMED GROUT OR ANY PORTLAND CEMENT BASED NON-SHRINK GROUT INTO THE CUT.

 **LITEACCESS**
TECHNOLOGIES INC
LA336MID-PNL.IPR.DWG

MICRODUCT 3/36 CABLE SYSTEM

MIN BEND RAD:
THIN DIRECTION: 140mm
WIDE DIRECTION: 300mm

MAX INSTALLATION PULL FORCE: 800N (80kg)

OUTER SHEATH REMOVAL: SHEATH CUTTERS WITH CARE

INNER SHEATH REMOVAL: USE RIPCORD PROVIDED

TOP OF UTILITY CANNOT BE CLOSER THAN 20mm (3/4") TO THE SURFACE

FOLLOW EXPANSION JOINT, COLD JOINT, PANEL JOINT, OR GUTTER EDGE WHEREVER POSSIBLE. CONSULT WITH MUNICIPAL OR ROW AUTHORITY PRIOR TO BEGINNING WORK. COMPLY WITH LOCAL REGULATIONS REGARDING SAW CUT RESTORATION FOR THIS TYPE OF SURFACE COVER.

SAWCUT DETAIL - CONCRETE SURFACE

- MID PANEL BEND - SCALE: N.T.S. - UPDATED 20070804

DISCLAIMER

THE LOCATIONS OF UTILITIES OR STRUCTURES SHOWN ON THIS DRAWING ARE APPROXIMATE ONLY. AXISS TECHNOLOGIES, LLC & BSE HEREBY DISCLAIMS ANY RESPONSIBILITY TO THIRD PARTIES FOR THE ACCURACY OF THIS INFORMATION. PERSONS PERFORMING SURFACE INLAY WORK MUST CONTACT THE APPROPRIATE CALL-BEFORE-YOU-DIG SYSTEM TO ASCERTAIN THE LOCATION OF UNDERGROUND UTILITIES PRIOR TO PERFORMING ANY EXCAVATION, DRILLING, OR SAWCUTTING